# **D28 DUAL POWER** TOUCH-FREE ELECTRONIC WALL-MOUNTED FAUCET

### SPECIFICATIONS

an infrared sensor. For cold or premixed water. Powered by a 9V battery or a 9V transformer with an integrated 9V users remove their hands. battery backup system in case of power failure. Chrome plated body, other finishes available. Adjustable setting by remote control: sensor range, security time, delay in, Wall-mounted faucet. Combines a minimalistic design delay out, on-off and reset to factory settings.

#### OPERATION


Touch-free wall-mounted electronic faucet. Activated by The faucet will automatically activate when users place their hands in the sensor range and will stop once the

#### APPLICATION

with vandal resistant features. Helps washrooms stay clean and saves water. Easy installation. Long lasting even in the harshest installation sites. Ideal for shopping malls, sport facilities and entertainment centers.

TRODUCT AT A GEARCE				
Installation	Concealed wall-mounted			
Power Supply	• 9V battery • 9V transformer with backup system			
Operating pressure	0.5-8.0 BAR / 7.0-116.0 PSI			
Water supply	Cold and premixed water			
Water flow	5 LPM / 1.32 GPM Honeycomb TT Laminar			
Water Saving Options	Water saving option: 1.89 LPM / 0.5 GPM PCA spray			
Water temperature	70°C Maximum			
Security Time	90 seconds. Adjustable by remote control			

PRODUCT AT A GLANCE




OPTIONS				
OPTION	CODE			
Remote control	07100005			
Matching battery-powered soap dispenser	350920			
Matching transformer-powered soap dispenser	350925			
Iron frame	500100			


## **ORDERING INFORMATION**

MODEL	CODE	POWER	ADDITIONAL SPECIFICATIONS
D28 DUAL POWER B	352300	9V battery	Concealed installation
D28 DUAL POWER E	352400	9V transformer and backup system	
D28 DUAL POWER LE	352410	9V transformer and backup system	Concealed installation Long spout version 273mm/10.75"





D28 DUAL POWER B



D28 DUAL POWER E

