# **D28 DUAL POWER** TOUCH-FREE ELECTRONIC WALL-MOUNTED FAUCET

### SPECIFICATIONS

an infrared sensor. For cold or premixed water. Powered by IP67 dual power input box that allows the faucet to be users remove their hands. used with 9V battery or 9V transformer. Can be powered by a 9V transformer and an integrated back up system to be used with 9V lithium battery enabling the faucet to Wall-mounted faucet. Combines a minimalistic design be used normally in case of power failure. Chrome plated body, other finishes available. Adjustable settings by remote control: sensor range, security time, delay in, delay out, on-off and reset to factory settings.

#### OPERATION


Touch-free wall-mounted electronic faucet. Activated by The faucet will automatically activate when users place their hands in the sensor range and will stop once the

#### APPLICATION

with vandal resistant features. Helps washrooms stay clean and saves water. Easy installation. Long lasting even in the harshest installation sites. Ideal for shopping malls, sport facilities and entertainment centers.

Installation	Concealed wall-mounted			
Power Supply	• 9V battery • 9V transformer with backup system			
Operating pressure	0.5-8.0 BAR / 7.0-116.0 PSI			
Water supply	Cold or premixed water			
Water flow	5 LPM / 1.32 GPM Honeycomb TT Laminar			
Water Saving Options	Water saving option: 1.89 LPM / 0.5 GPM PCA spray			
Water temperature	70°C Maximum			
Security Time	90 seconds. Adjustable by remote control			

**PRODUCT AT A GLANCE** 



OPTIONS				
OPTION	CODE			
Remote control	07100005			
Matching battery-powered soap dispenser	350920			
Matching transformer-powered soap dispenser	350925			
Iron frame	500100			

This graph applies to 0.5 GPM option only.

## **ORDERING INFORMATION**

MODEL	CODE	POWER	ADDITIONAL SPECIFICATIONS
D28 DUAL POWER B	352300	9V battery	Concealed installation
D28 DUAL POWER E	352400	9V transformer and backup system	
D28 DUAL POWER LE	352410	9V transformer and backup system	Concealed installation Long spout version 273mm/10.75"



