D28LTOUCH-FREEELECTRONIC WALL-MOUNTED FAUCET

SPECIFICATIONS

Touch-free wall-mounted electronic faucet. Activated by an infrared sensor. For cold or premixed water. Powered their hands in the sensor range and will stop once the by a 9V battery or a 9V transformer. Chrome plated body, users remove their hands. other finishes available. Long spout version 275 mm / 10.82". Adjustable setting by remote control: sensor range, security time, delay in, delay out, on-off and reset to factory settings.


OPERATION

APPLICATION

Wall-mounted faucet. Combines a minimalistic design with vandal resistant features. Helps washrooms stay clean and saves water. Easy installation. Long lasting even in the harshest installation sites. Ideal for shopping malls, sport facilities and entertainment centers.

		FRODUCT AT A GLANCE	
	Installation	Concealed wall-mounted	
	Power Supply	• 9V battery • 9V Transformer	
	Operating pressure	0.5-8.0 bar / 7.0-116.0 PSI. For pressure over 8 bar use a pressure reducing valve	
	Water supply	Cold or premixed water	
	Water Saving Options	5 LPM / 1.32 GPM ;1.89 LPM / 0.5 GPM	
	Water temperature	70°C Maximum	
	Security Time	90 seconds. Adjustable by remote control	

PRODUCT AT A GLANCE




ORDERING INFORMATION	

MODEL	CODE	POWER	ADDITIONAL SPECIFICATIONS
D28 LB	352010	9V battery	
D28 LE	352110	9V transformer	Long spout
D28 LB AISI316	352015	9V battery	275 mm / 10.82"
D28 LE AISI316	352125	9V transformer	

ODTIONS

	OPTION	CODE
	Remote control	07100005
	Matching battery-powered soap dispenser	350920
	Matching transformer-powered soap dispenser	350925
	Iron frame	500100







www.sternfaucets.com