MEDICAL 1000 TE TOUCH-FREE ELECTRONIC WALL-MOUNTED FAUCET

SPECIFICATIONS

Touch-free wall-mounted electronic faucet. Mixer for water temperature adjustment for hot and cold water. Body integrated spout. Powered by 9V transformer. Latching solenoid valve is located inside the product. Auto shutoff after 90 seconds. Adjustable settings by remote control: security time, APPLICATION delay in, delay out, on-off and reset to factory settings.

OPERATION

Touch-free electronic faucet. The faucet is automatically activated when users place their hands in the sensor range and stops when users move away from the sensor range.

Touch-free faucet. Enables patients and medical personnel to wash hands without touching the faucet. Prevents cross contamination. Helps washrooms to stay cleaner. Ideal for hospitals, laboratories, dental clinics and commercial kitchens.


PRODUCT AT A GLANCE					
Installation	Exposed wall-mounted				
Power Supply	9V transformer				
Operating water pressure	0.5-5.0 BAR (7-72.5 PSI), for water pressure greater than 5.0 bar use a pressure reducing valve.				
Water supply	Hot and cold water				
Water flow	6 LPM / 1.58 GPM - SSR PCA stream				
Water Saving Options	4 LPM / 1 GPM ; 3 LPM / 0.8 GPM 1.89 LPM / 0.5 GPM ; 1.3 LPM 0.35 GPM - PCA spray				
Water temperature	70°C Maximum				
Security Time	90 seconds. Adjustable by remote control				


FLOW RATE vs PRESSURE 0.5 FLOW RATE (gpm) 0.4 0.3 0.2 0.0 0.0 10 20 30 40 50 60 70 80 LINE PRESSURE (BAR)

This graph applies to 0.5 GPM option only.

ORDERING INFORMATION				OPTIONS	
MODEL	CODE	POWER	ADDITIONAL FEATURES	OPTION	CODE
MEDICAL 1000 TE	314600	9V transformer	Exposed installation Body integrated spout Mixer for water temperature adjustment	Remote control	07100005









777 Passaic Avenue Clifton NI. 07012 USA: sternusa@sternfaucets.com International: info@sternfaucets.com Toll Free: 1-800-4364410

www.sternfaucets.com