

TUBULAR HD

TOUCH-FREE ELECTRONIC WALL MOUNTED HAND DRYER

SPECIFICATIONS

Touch free electronic hand dryer for wall mounted installations. Powered by 110V-120/220V-240VAC. Hand dryer will automatically shut off after being used for more than 60 seconds. Sensor settings can be customized by remote control.

OPERATION

Touch free electronic hand dryer .The hand dryer is activated automatically, the user places hands under the opening and the IR sensor sends a signal to the electronic unit air sending out air.

APPLICATION

High speed, high quality hand dryer with a sleek, vandal resistant design. For use in transport facilities, schools, stadiums, sports arenas and public washrooms.

ADVANTAGES

- Easy mounting back plate.
- HEPA filter for added hygienic properties.
- Full brass body or stainless steel 316 material.
- Various finishes available to match our faucets and soap dispensers.
- Matching touch free faucet and soap dispenser
- Long lasting, durable and vandal resistant.
- Air flow intensity adjustable by external button
- Adjustability with remote control: security time, detection range, delay out
- On/Off function to perform cleaning

PRODUCT AT A GLANCE

Installation	Wall mounted
Operating Voltage	110V-120/220V-240VAC, 50/60 HZ, 1.3-1.6KW
Motor Thermal Protection	Auto resetting thermostat turns unit off, 120V at 135°C (257°F), 24°V at 95°C (203°F)
Heater Thermal Protection	Auto resetting thermostat turns unit off at 85°C (185°F). Thermal fuse cuts unit at 142°V (288°F)
Standby Power	0.3-0.4W
Timing Protection	60 seconds auto shut off
Sensing Range	170 mm ± 20 mm, Self adjusting
Drip Proof	IP21

ORDERING INFORMATION


MODEL	CODE	POWER	ADDITIONAL FEATURES
TUBULAR HD	350030	110V-120/220V-240VAC	Concealed installation in dry walls
TUBULAR HD AISI316	350040		
TUBULAR DP HD	350020		Concealed installation in dry walls as well as concrete and brick walls
TUBULAR DP HD AISI316	350010		

OPTIONS


OPTION	CODE
Remote control	07100014
Matching transformer powered faucet	350400
Matching transformer powered soap dispenser	350927



TUBULAR HD



TUBULAR DP HD



Airflow intensity adjustment button



777 Passaic Avenue
Clifton NJ, 07012

USA: sternusa@sternfaucets.com
International: info@sternfaucets.com
Toll Free: 1-800-4364410
www.sternfaucets.com